

XIAMETER(R) PMX-200 SILICONE FLUID 1.5 CS

Version Revision Date: SDS Number: Date of last issue: 04/04/2016 2.1 11/19/2016 984597-00006 Date of first issue: 12/17/2014

SECTION 1. IDENTIFICATION

Product name : XIAMETER(R) PMX-200 SILICONE FLUID 1.5 CS

Product code : 00000000004088413

Manufacturer or supplier's details

Company name of supplier : Dow Corning Corporation

Address : South Saginaw Road

Midland Michigan 48686

Telephone : (989) 496-6000

Emergency telephone : 24 Hour Emergency Telephone : (989) 496-5900

CHEMTREC: (800) 424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Cosmetics

Solvent Intermediate

Cleaning/washing agents and additives

Process regulators, other than polymerization or vulcanization

processes

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids : Category 3

GHS label elements

Hazard pictograms



Signal Word : Warning

Hazard Statements : H226 Flammable liquid and vapor.

Precautionary Statements : Prevention:

P210 Keep away from heat/sparks/open flames/hot surfaces.

No smoking.

P233 Keep container tightly closed.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equip-

nent.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.



XIAMETER(R) PMX-200 SILICONE FLUID 1.5 CS

Version Revision Date: SDS Number: Date of last issue: 04/04/2016 2.1 11/19/2016 984597-00006 Date of first issue: 12/17/2014

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately

all contaminated clothing. Rinse skin with water/shower.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

Other hazards

Vapors may form explosive mixture with air.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Substance name : Decamethyltetrasiloxane

CAS-No. : 141-62-8

Chemical nature : Silicone

Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)	
Decamethyltetrasiloxane	141-62-8	>= 90 - <= 100	

SECTION 4. FIRST AID MEASURES

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with plenty of water.

Remove contaminated clothing and shoes.

In case of eye contact : Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and

delayed

None known.

uelayeu

Protection of first-aiders : No special precautions are necessary for first aid responders.

Notes to physician : Treat symptomatically and supportively.



XIAMETER(R) PMX-200 SILICONE FLUID 1.5 CS

Version 2.1

Revision Date: 11/19/2016

SDS Number: 984597-00006

Date of last issue: 04/04/2016 Date of first issue: 12/17/2014

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media :

: Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

Do not use a solid water stream as it may scatter and spread

fire.

Flash back possible over considerable distance. Vapors may form explosive mixtures with air. Fire burns more vigorously than would be expected.

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod-

ucts

Carbon oxides

Silicon oxides Formaldehyde

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment:

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec: :

tive equipment and emer-

gency procedures

Remove all sources of ignition.

Follow safe handling advice and personal protective

equipment recommendations.

Environmental precautions : Discharge into the environment must be avoided.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g. by containment or oil

barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for

containment and cleaning up

: Non-sparking tools should be used.

Soak up with inert absorbent material.

Suppress (knock down) gases/vapors/mists with a water spray

jet.

For large spills, provide diking or other appropriate



XIAMETER(R) PMX-200 SILICONE FLUID 1.5 CS

Version Revision Date: SDS Number: Date of last issue: 04/04/2016 2.1 11/19/2016 984597-00006 Date of first issue: 12/17/2014

> containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate

container.

Clean up remaining materials from spill with suitable

absorbent.

Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation Use with local exhaust ventilation.

Use only in an area equipped with explosion proof exhaust

ventilation.

Advice on safe handling Handle in accordance with good industrial hygiene and safety

practice.

Non-sparking tools should be used. Keep container tightly closed.

Keep away from heat and sources of ignition.

Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the

environment.

Keep in properly labeled containers. Conditions for safe storage

Keep tightly closed.

Keep in a cool, well-ventilated place.

Store in accordance with the particular national regulations.

Keep away from heat and sources of ignition.

Materials to avoid Do not store with the following product types:

> Strong oxidizing agents Organic peroxides Flammable solids Pyrophoric liquids Pyrophoric solids

Self-heating substances and mixtures

Substances and mixtures which in contact with water emit

flammable gases **Explosives** Gases



XIAMETER(R) PMX-200 SILICONE FLUID 1.5 CS

Version Revision Date: SDS Number: Date of last issue: 04/04/2016 2.1 11/19/2016 984597-00006 Date of first issue: 12/17/2014

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of	Control parameters / Permissible	Basis
		exposure)	concentration	
Decamethyltetrasiloxane	141-62-8	TWA	200 ppm	DCC OEL

Engineering measures

Processing may form hazardous compounds (see section

10).

Minimize workplace exposure concentrations.

Use only in an area equipped with explosion proof exhaust

ventilation.

Use with local exhaust ventilation.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to

maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are

unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided

by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other

circumstance where air purifying respirators may not provide

adequate protection.

Hand protection

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration specific to place of work. Take note that the product is flammable, which may impact the selection of hand protection. Wash hands before breaks and at the end of

workday.

Eye protection : Wear the following personal protective equipment:

Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Wear the following personal protective equipment: Flame retardant antistatic protective clothing.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Hygiene measures : Ensure that eye flushing systems and safety showers are

located close to the working place. When using do not eat, drink or smoke.



XIAMETER(R) PMX-200 SILICONE FLUID 1.5 CS

Version Revision Date: SDS Number: Date of last issue: 04/04/2016 2.1 11/19/2016 984597-00006 Date of first issue: 12/17/2014

Wash contaminated clothing before re-use.

These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may

require added precautions.

For further information regarding the use of silicones / organic oils in consumer aerosol applications, please refer to the guidance document regarding the use of these type of materials in consumer aerosol applications that has been developed by the silicone industry (www.SEHSC.com) or contact the Dow Corning customer service group.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : colorless

Odor : none

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

> 35 °C

Flash point : 57.2 °C

Method: Pensky-Martens closed cup

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Self-ignition : The substance or mixture is not classified as pyrophoric. The

substance or mixture is not classified as self heating.

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : 0.850

Solubility(ies)

Water solubility : No data available

Partition coefficient: n- : No data available



XIAMETER(R) PMX-200 SILICONE FLUID 1.5 CS

Version Revision Date: SDS Number: Date of last issue: 04/04/2016 2.1 11/19/2016 984597-00006 Date of first issue: 12/17/2014

octanol/water

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : 1.5 cSt

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

Flammable liquid and vapor.

Vapors may form explosive mixture with air. Can react with strong oxidizing agents.

When heated to temperatures above 150 °C (300 °F) in the presence of air, trace quantities of formaldehyde may be re-

leased.

Adequate ventilation is required.

See OSHA formaldehyde standard, 29 CFR 1910.1048 Hazardous decomposition products will be formed at elevated

temperatures.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products

Thermal decomposition : Formaldehyde

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.



XIAMETER(R) PMX-200 SILICONE FLUID 1.5 CS

Version Revision Date: SDS Number: Date of last issue: 04/04/2016 2.1 11/19/2016 984597-00006 Date of first issue: 12/17/2014

Ingredients:

Decamethyltetrasiloxane:

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: On basis of test data.

Skin corrosion/irritation

Not classified based on available information.

Product:

Species: Rabbit

Result: No skin irritation

Remarks: On basis of test data.

Ingredients:

Decamethyltetrasiloxane:

Species: Rabbit

Result: No skin irritation

Remarks: On basis of test data.

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Species: Rabbit

Result: No eye irritation

Remarks: On basis of test data.

Ingredients:

Decamethyltetrasiloxane:

Species: Rabbit

Result: No eye irritation

Remarks: On basis of test data.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Product:

Assessment: Does not cause skin sensitization.

Test Type: Human repeat insult patch test (HRIPT)

Species: Humans



XIAMETER(R) PMX-200 SILICONE FLUID 1.5 CS

Version Revision Date: SDS Number: Date of last issue: 04/04/2016 2.1 11/19/2016 984597-00006 Date of first issue: 12/17/2014

Remarks: On basis of test data.

Ingredients:

Decamethyltetrasiloxane:

Assessment: Does not cause skin sensitization.

Test Type: Human repeat insult patch test (HRIPT)

Result: negative

Remarks: On basis of test data.

Germ cell mutagenicity

Not classified based on available information.

Product:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: On basis of test data.

: Test Type: Chromosome aberration test in vitro

Result: negative

Remarks: On basis of test data.

: Test Type: Mutagenicity (in vitro mammalian cytogenetic test)

Result: negative

Remarks: On basis of test data.

Ingredients:

Decamethyltetrasiloxane:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Result: negative

Remarks: On basis of test data.

: Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: On basis of test data.

: Test Type: Mutagenicity (in vitro mammalian cytogenetic test)

Result: negative

Remarks: On basis of test data.

Carcinogenicity

Not classified based on available information.

IARC No ingredient of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.



XIAMETER(R) PMX-200 SILICONE FLUID 1.5 CS

Version Revision Date: SDS Number: Date of last issue: 04/04/2016 2.1 11/19/2016 984597-00006 Date of first issue: 12/17/2014

NTP No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Not classified based on available information.

Product:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat, male and female Application Route: inhalation (vapor) Symptoms: No effects on fertility. Remarks: On basis of test data.

Test Type: Uterotrophic assay

Species: Rat, female

Application Route: inhalation (vapor)

Result: negative

Remarks: On basis of test data.

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat, male and female Application Route: inhalation (vapor)

Symptoms: No effects on fetal development.

Remarks: On basis of test data.

Reproductive toxicity - As-

sessment

No evidence of adverse effects on sexual function and fertility,

or on development, based on animal experiments.

Ingredients:

Decamethyltetrasiloxane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat, male and female Application Route: inhalation (vapor) Symptoms: No effects on fertility. Remarks: On basis of test data.

Test Type: Uterotrophic assay

Species: Rat, female

Application Route: inhalation (vapor)

Result: negative

Remarks: On basis of test data.

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat, male and female
Application Route: inhalation (vapor)

Symptoms: No effects on fetal development.



XIAMETER(R) PMX-200 SILICONE FLUID 1.5 CS

Version Revision Date: SDS Number: Date of last issue: 04/04/2016 2.1 11/19/2016 984597-00006 Date of first issue: 12/17/2014

Remarks: On basis of test data.

Reproductive toxicity - As-

sessment

No evidence of adverse effects on sexual function and fertility,

or on development, based on animal experiments.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Product:

Routes of exposure: Ingestion

Assessment: No significant health effects observed in animals at concentrations of 100 mg/kg

bw or less.

Routes of exposure: inhalation (vapor)

Assessment: No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or

less.

Ingredients:

Decamethyltetrasiloxane:

Routes of exposure: Ingestion

Assessment: No significant health effects observed in animals at concentrations of 100 mg/kg

bw or less.

Routes of exposure: inhalation (vapor)

Assessment: No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or

less.

Repeated dose toxicity

Product:

Species: Rat

Application Route: Ingestion Remarks: On basis of test data.

Species: Rat

Application Route: inhalation (vapor) Remarks: On basis of test data.

Ingredients:

Decamethyltetrasiloxane:

Species: Rat

Application Route: Ingestion Remarks: On basis of test data.

Species: Rat

Application Route: inhalation (vapor) Remarks: On basis of test data.



XIAMETER(R) PMX-200 SILICONE FLUID 1.5 CS

Version Revision Date: SDS Number: Date of last issue: 04/04/2016 2.1 11/19/2016 984597-00006 Date of first issue: 12/17/2014

Aspiration toxicity

Not classified based on available information.

Further information

Ingredients:

Decamethyltetrasiloxane:

Remarks: This material contains decamethyltetrasiloxane (L4). Repeated oral exposure in rats to L4 resulted in protoporphyrin accumulation in the liver. Without knowledge of the specific mechanism leading to the protoporphyrin accumulation the relevance of this finding to humans is unknown.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Ingredients:

Decamethyltetrasiloxane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 0.0063 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: No toxicity at the limit of solubility.

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 0.0055 mg/l

Exposure time: 48 h

Remarks: No toxicity at the limit of solubility.

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): >

0.0022 mg/l

Exposure time: 72 h

Test Type: Growth inhibition

Remarks: No toxicity at the limit of solubility.

Toxicity to fish (Chronic tox-

icity)

LC50 (Oncorhynchus mykiss (rainbow trout)): > 0.0056 mg/l

Remarks: No toxicity at the limit of solubility.

NOEC (Oncorhynchus mykiss (rainbow trout)): >= 0.0056 mg/l

Remarks: No toxicity at the limit of solubility.

NOEC (Oncorhynchus mykiss (rainbow trout)): >= 0.0079 mg/l

Method: OECD Test Guideline 210 Remarks: On basis of test data. No toxicity at the limit of solubility.

Toxicity to daphnia and other : aquatic invertebrates (Chron-

NOEC (Daphnia magna (Water flea)): 0.0049 mg/l Exposure time: 21 d

ic toxicity)

Method: OECD Test Guideline 211 Remarks: On basis of test data. No toxicity at the limit of solubility.



XIAMETER(R) PMX-200 SILICONE FLUID 1.5 CS

Version Revision Date: SDS Number: Date of last issue: 04/04/2016 2.1 11/19/2016 984597-00006 Date of first issue: 12/17/2014

Ecotoxicology Assessment

Chronic aquatic toxicity This product has no known ecotoxicological effects.

Persistence and degradability

No data available

Bioaccumulative potential

Ingredients:

Decamethyltetrasiloxane:

Bioaccumulation Species: Fish

> Bioconcentration factor (BCF): >= 500 Method: OECD Test Guideline 305

Remarks: Does not biomagnify along the food chain.

Partition coefficient: n-

octanol/water

log Pow: > 8

Remarks: On basis of test data.

Mobility in soil No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Resource Conservation and

Recovery Act (RCRA)

When a decision is made to discard this material as supplied,

it is classified as a RCRA hazardous waste.

Waste Code D001: Ignitability

Waste from residues Dispose of in accordance with local regulations.

Contaminated packaging Empty containers should be taken to an approved waste

handling site for recycling or disposal.

Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or

death.

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG



XIAMETER(R) PMX-200 SILICONE FLUID 1.5 CS

Version Revision Date: SDS Number: Date of last issue: 04/04/2016 2.1 11/19/2016 984597-00006 Date of first issue: 12/17/2014

UN number : UN 1993

Proper shipping name : FLAMMABLE LIQUID, N.O.S.

(Decamethyltetrasiloxane)

Class : 3
Packing group : III
Labels : 3

IATA-DGR

UN/ID No. : UN 1993

Proper shipping name : Flammable liquid, n.o.s.

(Decamethyltetrasiloxane)

Class : 3 Packing group : III

Labels : Flammable Liquids

Packing instruction (cargo :

aircraft)

Packing instruction (passen: 355

ger aircraft)

333

366

IMDG-Code

UN number : UN 1993

Proper shipping name : FLAMMABLE LIQUID, N.O.S.

(Decamethyltetrasiloxane)

Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : NA 1993

Proper shipping name : Combustible liquid, n.o.s.

(Decamethyltetrasiloxane)

Class : CBL
Packing group : III
Labels : None
ERG Code : 128
Marine pollutant : no

Remarks : Above applies only to containers over 119 gallons or 450 li-

ters. Not regulated if shipped in packages less than or equal to 119 gallons (450 liters). If transporting by vessel or aircraft, unless other means of transportation is impracticable, then the

product must be shipped as a flammable liquid.



XIAMETER(R) PMX-200 SILICONE FLUID 1.5 CS

Version Revision Date: 2.1 11/19/2016

SDS Number: 984597-00006

Date of last issue: 04/04/2016 Date of first issue: 12/17/2014

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Fire Hazard

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

Decamethyltetrasiloxane 141-62-8

California Prop. 65 This product does not contain any chemicals known to the

State of California to cause cancer, birth, or any other repro-

ductive defects.

The ingredients of this product are reported in the following inventories:

NZIoC : All ingredients listed or exempt.

REACH : For purchases from Dow Corning EU legal entities, all

ingredients are currently pre/registered or exempt under REACH. Please refer to section 1 for recommended uses. For purchases from non-EU Dow Corning legal entities with the

intention to export into EEA please contact your DC

representative/local office.

TSCA : All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

AICS : All ingredients listed or exempt.

IECSC : All ingredients listed or exempt.

ENCS/ISHL : All components are listed on ENCS/ISHL or exempted from

inventory listing.

KECI : All ingredients listed, exempt or notified.

PICCS : All ingredients listed or exempt.

DSL : All chemical substances in this product comply with the CEPA



XIAMETER(R) PMX-200 SILICONE FLUID 1.5 CS

Version Revision Date: SDS Number: Date of last issue: 04/04/2016 2.1 11/19/2016 984597-00006 Date of first issue: 12/17/2014

1999 and NSNR and are on or exempt from listing on the


Canadian Domestic Substances List (DSL).

TCSI : All ingredients listed or exempt.

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Special hazard.

HMIS® IV:

HEALTH	/ 0
FLAMMABILITY	2
PHYSICAL HAZARD	0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

DCC OEL : Dow Corning Guide
DCC OEL / TWA : Time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance: ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan): ISO - International Organisation for Standardization: KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR -No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development;



XIAMETER(R) PMX-200 SILICONE FLUID 1.5 CS

Version Revision Date: SDS Number: Date of last issue: 04/04/2016 2.1 11/19/2016 984597-00006 Date of first issue: 12/17/2014

OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 11/19/2016

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8