



CERTIFICATE OF ANALYSIS: KETRUL D95 (NOW AVAILABLE)

Client Name: **Product Origin:** Bayport
Delivery Location: **Loading Location:** 11666 Port Rd, Seabrook, Texas
77586

Client PO: **TC SO:**
Client Material Ref:
Bill of Lading Date: 9/9/2016 **Batch Ref:**
Bill of Lading Ref: **Batch Date:** 6/27/2016
Trailer / Railcar Ref: **lbs/Gallon:** 6.7781

Name	Unit	Method	Min Value	Max Value	Result
Flash Point (Pensky-Martens)	°F (°C)	ASTM D93	200 (93.5)		210 (99.0)
Viscosity at 104°F (40°C)	mm ² /s	ASTM D445	2.00	3.50	3.16
Aromatic content (UV)	ppm	UV		300	266
Appearance at 15°C		Visual	Clear & Bright		Clear & Bright
Saybolt color		ASTM D156	+30		+30
Dry Point	°F (°C)	ASTM D86		626 (330)	601 (316.2)
Initial Point	°F (°C)	ASTM D86	410 (210)		436 (224.4)
Density at 59°F (15°C)	kg/m ³	ASTM D4052	800	840	812.2

The results given are those based on representative samples, and are not necessarily those of the product actually shipped.

Name & Signature: Bayport TPRI Laboratory