

 <p>THE DOW CHEMICAL COMPANY</p>	<p>Ship From: Erstein PU-SH</p> <p>ERSTEIN France</p>																		
<p align="center"><b>Certificate of Analysis</b></p> <p>Product Number 00099017257</p> <p>Product Name HYPERLAST™ FJ 760E Polyol</p> <p>Delivery No.</p> <p>Order Number</p> <p>Shipping Units 3.000 DR</p> <p>Date Shipped 2020-10-06 (YYYY-MM-DD)</p> <p>Shipment No.</p>	<p align="center"><b>Customer Information</b></p> <p>Customer Name</p> <p>Customer PO number</p> <p>Container ID</p> <p>Vehicle#</p> <p>Specification Number</p>																		
<p>Batch Number</p> <p>Expiration Date 2021-09-30 (YYYY-MM-DD)</p> <p>Manufacturing Date 2020-09-30 (YYYY-MM-DD)</p> <p>Quantity 3.000 DR</p> <p>Net Weight 1322.775 LB</p> <p>Packaging Information 200 KG TIGHT HEAD DRUM</p>																			
<table border="1"> <thead> <tr> <th>Test</th> <th>Unit</th> <th>Lower Limit</th> <th>Upper Limit</th> <th>Value</th> <th>Method</th> </tr> </thead> </table>		Test	Unit	Lower Limit	Upper Limit	Value	Method												
Test	Unit	Lower Limit	Upper Limit	Value	Method														
<table border="1"> <tbody> <tr> <td><b>Appearance</b></td> <td>-</td> <td>-</td> <td>-</td> <td>Pass</td> <td>DOWM 101967</td> </tr> <tr> <td><b>Gel Time</b></td> <td>min</td> <td>2.50</td> <td>3.50</td> <td>3.25</td> <td>SH-PM-12</td> </tr> <tr> <td><b>Hardness</b> Shore A 1hour/80degC</td> <td></td> <td>84</td> <td>-</td> <td>89</td> <td>ASTM D2240</td> </tr> </tbody> </table>		<b>Appearance</b>	-	-	-	Pass	DOWM 101967	<b>Gel Time</b>	min	2.50	3.50	3.25	SH-PM-12	<b>Hardness</b> Shore A 1hour/80degC		84	-	89	ASTM D2240
<b>Appearance</b>	-	-	-	Pass	DOWM 101967														
<b>Gel Time</b>	min	2.50	3.50	3.25	SH-PM-12														
<b>Hardness</b> Shore A 1hour/80degC		84	-	89	ASTM D2240														
<p>For inquiries please contact Customer Service or local sales</p> <p>® ™ Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow</p>																			