

## TECHNICAL DATA SHEET

# CN973H85

Aromatic Urethane Acrylate blended with EOEOEA (SR256)

CN973H85 is an aromatic polyester based urethane diacrylate oligomer blended with 15% SR256, 2(2-ethoxyethoxy) ethyl acrylate. It is a highly flexible oligomer.



#### **SHELF LIFE**

Store in the original, closed container in a dry, cool (<45°C) and well-ventilated place. Keep away from frost and heat (open flames, hot surfaces and sources of ignition) sources. Typical shelf-life is 6 months from delivery date for unopened containers. In cases where product sampling is required to carry out incoming quality tests, shelf-life should be maintained beyond opening, provided that it is tightly closed immediately after and that contamination with foreign bodies is avoided. Inhibitors have been added to enhance storage stability. They require the presence of air in the container in order to improve their efficiency. Keep stabilizer levels constant to avoid explosive polymerization. An air space is required above the liquid in all containers

#### **STORAGE**

See SDS for Storage Considerations

#### **HEALTH AND SAFETY**

See SDS for Health & Safety Considerations

# **LIQUID PROPERTIES**

Clear liquid Functionality Color (Pt/Co or APHA) <100 Density at 25°C (g/mL) 1.0741 Refractive Index at 25°C 1.4784

### **CURED PROPERTIES**

Tg (°C), by DSC -36 Elongation at break (%) 122 Tensile Strength (MPa) Young Modulus (MPa)

#### **PRODUCT PERFORMANCE**

Flexibility Wood Adhesion ABS/PC Adhesion Metal Adhesion PVC/PS Adhesion PE/PET/PP/PMMA Adhesion Shrinkage Weatherability Chemical Resistance Moisture Resistance Corrosion Resistance

#### **SUGGESTED APPLICATIONS**

Adhesives & sealants Electronics Flexographic inks Inkjet inks Metal coatings Overprint varnishes Plastic coatings Wood coatings

Arkema Inc 502 Thomas Jones Way Exton, PA 19341 – AMERICA

**Arkema France** 420, rue d'Estienne d'Orves 92705 Colombes Cedex France www.Sartomer.arkema.com



