

Technical Data Sheet

RUBINATE® 9009 MDI

Diphenylmethane Diisocyanate Polyurea Prepolymer

DESCRIPTION

RUBINATE 9009 MDI Isocyanate is a member of the Polyurea Prepolymer isocyanate family. These materials are designed to be used in combination with resin blends containing JEFFAMINE® Polyetheramines and/or JEFFOL® Polyether Polyols for the production of high-performance polyurea coatings and elastomers.

RUBINATE 9009 MDI has been developed to provide improved physical properties and quicker return-to-service than other alternative products.

Typical Properties	
Color	Pale Yellow Liquid
Isocyanate Equivalent Weight	266
NCO content, %	15.8
Viscosity at 77°F (25°C), cps	1200
Specific Gravity at 77°F (25°C)	1.12
Flash Point, (SetaFlash Closed Cup) °C (°F)	>110 (>230)
Vapor Pressure at 77°F (25°C) (mm Hg)	< 10 ⁻⁵
Functionality	2.13
Recommend Storage Temperature	60-100°F (16-38°C)
Shelf Life	6 Months

APPLICATIONS

Huntsman Polyurethanes offers a wide range of MDI prepolymers for polyurea applications such as industrial maintenance, secondary containment and geotextiles. Please consult with your Huntsman Polyurethanes Sales Representative for specific end-use information.

Note: Products made from RUBINATE 9009 MDI will yellow with exposure to UV light (including sunlight). Users should make their own tests to determine the suitability of this product for their own particular purposes.

HANDLING AND STORAGE

The reaction of isocyanates with water leads to the formation of insoluble ureas and carbon dioxide gas which can result in pressure build-up inside closed containers. Therefore, extreme care must be taken to ensure containers used for RUBINATE 9009 MDI remain dry. Containers that have become contaminated with moisture should not be subsequently sealed; otherwise a hazardous increase in pressure may result.

Freshly manufactured RUBINATE 9009 MDI is a pale yellow liquid. Sedimentation is usually due to contamination from atmospheric moisture or to dimer formation. Reaction from atmospheric moisture can be prevented by storing RUBINATE 9009 MDI in carefully sealed containers or under a dry nitrogen atmosphere. During handling, RUBINATE 9009 MDI must also be protected from atmospheric moisture and water ingress, and containers must be carefully resealed after each sampling.

A small amount of finely divided insoluble solid in the liquid product does not usually cause difficulties in handling or product performance. However, if necessary, the liquid product may be filtered through a suitable in-line filter. It is suggested that the filter vessel be of stainless steel with a suitable polypropylene filter bag. The lines should be heated and blown clear with nitrogen after use.

RUBINATE 9009 MDI is also available in 55-gallon drums. If drums have been exposed to temperatures below the recommended storage temperatures for more than a few hours, the material may increase in viscosity. If this occurs, the product may be heated to room temperature to reduce viscosity.

HEATING AND MELTING

MDI variants may require heating to 60-100°F (16-38°C), their normal operating temperatures.

Certain variants must be heated to 158-174°F (70-80°C) if they have become chilled and crystals have formed. Heating and melting should be carried out with extreme caution. Heating and melting are usually performed in one or several ways:

Hot Air Oven or Chamber: Drums are heated by hot air using drum rollers to reduce heating time. Drums must remain sealed while heating. For pure MDI, heating must be rapid to avoid deterioration of the product. Care must be taken so that the drum is not damaged in order to maintain its integrity during the melting process.

Water Baths or Steam Chests: Only unopened containers should be treated with ambient steam or in water baths. Take extreme care to ensure that water and water vapor do not enter the drum. To do this, tighten the bung and apply dust caps. Failure to do so may result in a build-up of pressure in the drum due to vapor contamination.

NEVER heat MDI by open flames, hot plates or any other method of direct heating.

No matter which method you use, you must carefully inspect drums before heating to ensure they are not damaged. When liquid MDI is heated, MDI vapor in the air increases. Vapor also increases when the drum is opened, and during open pouring. Regular monitoring is important to assess airborne levels.

Drums should be stored at temperatures of 60-100°F (16-38°C). After use, empty containers should not be disposed of until all hazardous residue has been removed. Remove container from work area, preferably outdoors, or in a well ventilated area. Fill container with decontamination solution containing 3-8% ammonia and 0.2-0.5% detergent and allow to stand for 48 hours. Do not seal or otherwise close bungs in container. After draining the container, puncture or crush it in accordance with waste disposal regulations.

REACTIVITY HAZARD

RUBINATE 9009 MDI is an organic isocyanate and, as such, requires care in handling because it reacts with water and organic compounds containing active hydrogen groups. Because the reaction of RUBINATE 9009 MDI with water produces carbon dioxide gas, containers that have become contaminated with moisture should not be subsequently sealed; otherwise, pressure build-up will result.

ATTENTION

This product is sold solely for use by industrial institutions. Please refer to the Material Safety Data Sheet (MSDS) regarding regulatory compliance, safety, hazards, spill procedures and disposal of this product.

For Your Protection**HEALTH AND SAFETY**

The Safety and Health information in this data sheet does not contain sufficient detail for safe handling in all cases. For detailed safety and health information refer to the Material Safety Data Sheet for this product.

EMERGENCY CALLS: Huntsman Emergency Response Center: 800-328-8501, 409-722-8381 / CHEMTREC - Spills, Leak, Fire 800-424-9300 (in USA and Canada)

IMPORTANT LEGAL NOTICE: Sales of the products described herein ("Product") are subject to the general terms and conditions of sale of Huntsman Corporation and its affiliates and subsidiaries (collectively, "Huntsman").

To the knowledge, information and belief of Huntsman, all the information and recommendations in this publication are accurate as of the date of publication.

WARRANTY:

Huntsman warrants that at the time and place of delivery all Products sold to a buyer of such Products shall conform to the specifications provided by Huntsman to such buyer of such Products.

DISCLAIMER AND LIMITATION OF LIABILITY:

EXCEPT AS SET FORTH ABOVE, HUNTSMAN MAKES NO OTHER WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, NONINFRINGEMENT OF ANY INTELLECTUAL PROPERTY RIGHT OF ANY THIRD PARTY, OR WARRANTIES AS TO QUALITY OR CORRESPONDENCE WITH PRIOR DESCRIPTION OR SAMPLE, AND ANY BUYER OF PRODUCTS DESCRIBED HEREIN ASSUMES ALL RISK AND LIABILITY WHATSOEVER RESULTING FROM THE USE OF SUCH PRODUCT, WHETHER USED SINGLY OR IN COMBINATION WITH OTHER SUBSTANCES. Chemical or other properties purported to be typical of such Products, where stated herein, should be considered as representative of current production and should not be construed to be specifications of any such Products. In all cases, it is the sole responsibility of a buyer to determine the applicability of the information and recommendations contained in this publication and the suitability of any Product for its own particular purpose, and no statements or recommendations made herein are to be construed as a suggestion, recommendation, or authorization to take any action that would infringe any patent or other intellectual property right. A buyer or user of a Product is solely responsible for ensuring that its intended use of such Product does not infringe any third party's intellectual property rights. Huntsman's maximum liability for any claim related to the Products described herein or breach of an agreement associated therewith shall be limited to the purchase price of the Products or portion thereof to which such claim pertains. IN NO EVENT SHALL HUNTSMAN BE LIABLE FOR ANY CONSEQUENTIAL, INCIDENTAL, SPECIAL OR PUNITIVE DAMAGES, INCLUDING BUT NOT LIMITED TO ANY DAMAGES FOR LOST PROFITS OR BUSINESS OPPORTUNITIES OR DAMAGE TO REPUTATION.

WARNING:

The behaviour, hazardousness and/or toxicity of the Products referred to in this publication in manufacturing processes and their suitability in any given end-use environment are dependent upon various conditions such as chemical compatibility, temperature, and other variables, which may not be known to Huntsman. It is the sole responsibility of the buyer or user of such Products to evaluate the manufacturing circumstances and the final Product(s) under actual end-use requirements and to adequately advise and warn future purchasers and users thereof.

Products referred to in this publication may be hazardous and/or toxic and require special precautions in handling. A buyer should obtain Material Safety Data Sheets from Huntsman containing detailed information on hazardousness and/or toxicity of the products contained herein, together with proper shipping, handling and storage procedures, and should comply with all applicable safety and environmental standards. The Product(s) described herein have not been tested for, and is therefore not recommended or suitable for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended or likely, or for uses for which implantation within the human body is intended, and Huntsman assumes no liability for such uses.

Unless otherwise specified, Huntsman shall not be liable for or otherwise have any obligation to a buyer of any Products contained in this publication for any technical or other information or advice furnished by Huntsman in this publication.

RUBINATE®, JEFFOL® and JEFFAMINE® are registered trademarks of Huntsman Corporation or an affiliate thereof in one or more, but not all countries.

Copyright © 2010 Huntsman Corporation. All rights reserved.

Approved: Kevin A Buck

For further information, please visit our website at: www.huntsman.com/pu/ACE